

baler wires



Cut & looped straight lengths baler wire

SPECIFICATION

Qualities	black annealed mild steel wire.		350 MN/m ² (49000 lbf/in ²) minimum						
	black annealed high tensile wire.		494 MN/m ² (71000 lbf/in ²) minimum						
	annealed galvanized mild steel wire.		386 MN/m ² (56000 lbf/in ²) minimum						
Packing	adequately tied into 25 kg (55lb) bundles. Polythene packed both ends.								
Finish	oiled or dry.								
Range (mm)	1.60	1.80	2.00	2.36	2.65	3.00	3.25	3.55	3.75
(ins)	0.063	0.071	0.080	0.09	0.105	0.118	0.128	0.140	0.147
Length	1.5m - 4.6m 5ft - 15ft			1.5m - 6.1m 5ft - 20ft					

Re-wound baler wire

SPECIFICATION

Coil Dimensions I.D. O.D. Depth	Coil weight	No. of binders per coil	Coil wrapping	Carton	Finish	Qualities	
206-336-150mm 8½"-13¼"-6"	45 kg 100lbs	6	waxed paper	bound with 2 straps	oiled or dry	black annealed mild steel (49000 lbf/in ²) black annealed high tensile wire (71000 lbf/in ²) annealed galv. mild steel (56000 lbf/in ²)	
Range (mm)	1.83	1.93	2.00	2.36	2.65	3.00	3.15
(ins)	0.072	0.075	0.079	0.092	0.104	0.118	0.123
Length (m)	2211	1981	1830	1310	1050	800	740
(feet)	7250	6500	6,000	4,380	3,440	2,660	2,410

Any non-standard size between 2.00mm and 3.75mm can be produced to order.

Coil dimensions: I.D. 45mm (1¾") O.D. 127mm (5") depth 32mm (1¼").